


Socket type

Part No.: **PN-3-1-C** (10pcs/pack)

- This is a socket type and OP-1 is suitable as the male pin.
- Material Pin part: Brass
 - Contact part: Beryllium copper
 - Resin part (main body): 9T nylon (UL94V-0)
 - Nut: Brass, Nickel plating
- Finish Pin part: Gold plating over nickel base
 - Contact part: Gold plating over nickel base
- Resin color: BLACK, RED, YELLOW, GREEN, BLUE, WHITE
- Adaptive male pin diameter: ϕ 0.45 to ϕ 0.6
- Rated current: 1A
- Thickness of panel that can be fit: 0.5mm to 5.0mm
- Panel fitting hole diameter: ϕ 3.2




How to order

PN-3-1-C YELLOW

↑ Please specify the resin color.
(BLACK, RED, YELLOW, GREEN, BLUE or WHITE)

- See the bottom of the page for specifications and precautions for use.



PN-C series specifications and precautions for use

Specification (PN-C series)

Rated current	3A 1A (only PN-3-1-C)
Rated voltage	125V AC, DC
Withstand voltage	1000V AC, DC
Insulation resistance	500M Ω or over
Operating temperature range	- 20 to + 100°C

- Do not strongly tighten the nut when fitting. (Tightening torque of 1.0 kgf-cm (9.8 N-cm) or over is not allowed.)
- Please fix by using a screw lock.